

TRANSPORTER ◀ 6030T



XROK TRANSPORTER 6030T

Sustainable and multifunctional stockpile conveyor

XROK

TRANSPORTER ◀ 6030T



SUSTAINABLE AND MULTIFUNCTIONAL STOCKPILE CONVEYOR

Applications

The Transporter 6030T tracked conveyor is designed to process stones, aggregate, minerals, solid waste, topsoil, compost and green waste type products.

Benefits and advantages

- Steady and smooth operation, low noise and low energy consumption
- Robust, heavy duty construction allows a wide variety of materials
- Simple structure
- Maintenance friendly with full service accessibility and central grease points
- Hydraulic cylinders to adjust height
- Simple and quick installation
- DSE display panel
- Movable by remote
- 6880 mm stockpile height
- Capacity up to 500 TPH
- Minimal set-up time
- Long service interval

Dimensions


Chassis	Steel tracks (400 mm)
Gross weight	8000 (kg)
Working Length	18000 (mm)
Width	2220 (mm)
Height (max.)	7040 (mm)
Transport length	11690 (mm)
Transport width	2220 (mm)
Transport height	2460 (mm)

Power unit


Engine	Caterpillar C2.2 (Diesel)
Engine power	49HP (36kW)
Fuel	Diesel

Conveyor


Length	18000 (mm)
Width	785 (mm)
Type	EP400 3 ply conveyor belt



Hydraulic pump
33cc Vivoli



Cat C2.2 motor
49HP (36kW)



Hydraulic controls



Remote control

